

FIBER SPECIFICATIONS		
COLOR CODE	WHITE	ORANGE
FIBER TYPE	DOUBLE-CLAD FIBER	MULTIMODE FIBER
CORE DIAMETER (NOMINAL)	4 µm	200 µm
CORE NA	0.19	0.26
CUT-OFF WAVELENGTH	≤960 nm	-
INNER CLADDING DIAMETER	102 µm	-
INNER CLADDING NA	0.24	-
OUTER CLADDING DIAMETER	125 µm	220 µm



ISOMETRIC VIEW
SCALE 1:4



COUPLER SPECIFICATIONS	
WAVELENGTH RANGE	960 - 1260 nm
SM CORE INSERTION LOSS	≤0.5 dB
MM INNER CLAD TRANSFER	≥60%
OPERATING TEMPERATURE °C	-40 °C TO 85 °C
STORAGE TEMPERATURE °C	-40 °C TO 85 °C
ALL SPECIFICATIONS ARE GIVEN BASED ON NON-CONNECTORIZED MODELS	

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION		
	NAME	DATE
DRAWN	DB	25/Jan/16
APPROVAL	PB	03/Feb/16

COPYRIGHT © 2016 BY THORLABS

VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS

THORLABS
www.thorlabs.com

Double-Clad Fiber Coupler, 1060nm

MATERIAL	REV
N/A	B

ITEM #	APPROX WEIGHT
DC1060LEFA	0.11 kg